



CAMBUT

AG ELECTRONICS

MINI GAC™ 2500

Grain Moisture Analyser



The most accurate handheld moisture tester that provides fast and easy results. Now with 149 MHz - UGMA technology to match the new moisture testers at the elevator.

Measuring grain moisture straight from the field has never been easier than with the DICKEY-john® mini GAC™ 2500 handheld grain moisture analyzers. This handheld moisture tester offers the highest level of accuracy in its class, plus the mini GAC™ is fast and easy to use.

Features and Benefits:

- Simplifies operation with menu-driven interface
- Eliminates pre-weighing with an internal scale
- Avoids cumbersome screw caps that can cause grain damage and oily residue
- Measures over 250 types of grain product
- Easily loads calibrations with a USB
- Tests hot or cold grain between -18 and 75°C
- Receives accurate measurements in a variety of conditions with automatic temperature compensation



DICKEY-john®
A DIVISION OF TSI®

Cambut AG Electronics

6/139 Sandgate Road
Albion QLD 4010 AUSTRALIA
Phone: +61 7 3391 8766
WhatsApp: +60 17 916 3579
email: apac@cambut.com.au
Web: www.cambut.com.au

www.cambut.com.au

MINI GAC™ 2500

Grain Moisture Analyser

Unit Specifications

Measurement method	149 MHz - UGMA technology, internal scale, temperature
Moisture range	5 - 45% (depending on grain type)
Grain temperature	-18 and 75°C
Temperature difference	20°C instrument to grain sample
Temperature compensation	automatic
Grain type	whole grain, no sample preparation
Sample size	0.47 L
Display	LCD (106 x 56 pixels)
Analyzer height*	11.9 in (30.2 cm)
Analyzer width*)	4.8 in (12.2 cm)
Analyzer depth*	8.3 in (21.1 cm)
Weight (total)	2 lbs 7 oz (1.1 kg)
Measured parameters	moisture, grain temperature and test weight

Moisture Measurement Specifications

Moisture repeatability	0.3% moisture, depending on grain type, in commercial trade range, typical
Moisture resolution	0.1% moisture

Grain Temperature Measurement Specification

Accuracy	10.5°C
Temperature resolution	0.1°C

Test Weight Specifications

Repeatability	0.5 lb/bu (0.6 kg/h) in commercial trade range, depending on grain type
Test weight resolution	0.1 lb/bu (kg/hl)

Other Specifications

Operating temperature	(5 - 45°C)
Humidity	5 - 95% non-condensing
Power	9 VDC battery (Installed)

Backed by the power of DICKEY-john:

When you buy a DICKEY-john GAC™ 2700-AGRI you get all the dependability and value you expect from DICKEY-john® products. Like all DICKEY-john products, the GAC 2700-AGRI is designed and manufactured in the USA, and supported worldwide.



Intuitive Color Touchscreen



Multiple Back USB Ports



Easy-to-Read Results Screen



www.cambut.com.au



6/139 Sandgate Road
Albion QLD 4010 AUSTRALIA
Phone: +61 7 3391 8766
WhatsApp: +60 17 916 3579
email: apac@cambut.com.au
Web: www.cambut.com.au

DICKEY-john, the DICKEY-john Logo are registered trademarks of TSI Incorporated in the United States and may be protected under other country's trademark registrations.